

# biofoam



 **Vétoquinol**  
*a Sign of Passion*

**FOAMING  
DESCALING  
DETERGENT**

**CLEANER**

Vétoquinol N.-A. Inc.  
2000 chemin Georges  
Lavaltrie, Quebec, Canada J5T 3S5 1-800-363-1700  
[www.vetoquinol.ca](http://www.vetoquinol.ca)  
Manufactured by: Antec International [www.antecint.com](http://www.antecint.com)



# biofoam

## FOAMING DESCALING DETERGENT

- **Powerful foaming cleaning concentrate**
- **Superior descaling properties**
- **For use in food processing hatcheries & on the farm**
- **Biodegradable**

### COMPOSITION:

A synergistic blend of surfactants that combine to produce a superior foaming cleaner, preventing scale build-up.

### GENERAL PROPERTIES:

- Excellent cleaning and degreasing properties
- Superior foaming properties
- Can be used as a foam or a spray
- May be used with pressure washers or spraying equipment
- Suitable on all hatchery, processing and farm surfaces
- Non-staining
- Non-tainting
- Biodegradable

CLEANER

### APPLICATIONS:

For the removal of organic and inorganic residues, particularly scale build-up, Biofoam is ideal for the removal of soiling in hatcheries and in processing plants where humidity can cause soil and scale build-up. Biofoam also helps to remove stubborn stains and soiling on factory floors and on slats on livestock farms.

### DIRECTIONS FOR USE:

- **DILUTION RATES** - For normal use, Biofoam should be used at a dilution between 1% - 5%, depending on the soiling and scaling levels. In situations where there is a thick build-up of scaling and soil, it may be necessary to use Biofoam at a higher concentration of up to 10%.
- **SPRAYING** - Apply at a rate of 500 ml/m<sup>2</sup> with either a knapsack sprayer or a pressure washer. The pressure washer should be set at a low pressure setting (500 psi - 35 bars) using a 45-degree jet angle. Hot water will improve the product's effectiveness. Allow a contact time of 15 minutes before rinsing all surfaces thoroughly with water at high pressure (3000 psi - 207 bars).
- **FOAMING** - Apply at a rate of 250 ml/m<sup>2</sup> with a pressure washer set at a low pressure setting (500 psi - 35 bars). Hot water will improve the product's effectiveness. Allow a contact time of 15 minutes before rinsing all surfaces thoroughly with water at high pressure (3000 psi - 207 bars).
- **STAIN REMOVAL** - For stubborn stains and scale build-up, Biofoam may be used undiluted.

### PRECAUTIONS:

- Avoid contact with eyes and skin when handling this product.
- Do not breathe the spray mist (a mist respirator is recommended where appropriate).
- Wear suitable protective clothing, gloves, eye and face protection.
- Store in a cool place out of direct sunlight. Do not allow to freeze.
- Do not allow the product to enter streams and rivers.
- Keep out of the reach of children.

### EMERGENCY / FIRST AID PROCEDURES:

- If the product (diluted or undiluted) is splashed in the eyes, rinse immediately with plenty of water and seek medical advice.
- Rinse any product off the skin immediately with water.
- If ingested, have the person drink water if conscious, but do not induce vomiting. Seek medical advice.

### STORAGE:

- Store in a cool dry place away from other products.

### DISPOSAL:

Dilute small quantities for disposal into waste-water, via a sanitary sewer or other treatment facility in accordance with local water authority regulations.

### SHELF LIFE:

Concentrate: 3 years. Diluted product: up to one week if unused.

### PACKAGING:

Available in 20 litre drums complying with UN standards.

Distributed in Canada by Syndel Laboratories Ltd  
2595 McCullough Road  
Nanaimo, BC, Canada V9S 4M9  
Tel.: 800-663-2282  
Fax: 250-585-5300  
[www.syndel.com](http://www.syndel.com)