

VÉTOQUINOL CANADA INC.

2000, CHEMIN GEORGES, LAVALTRIE, QC, J5T 3S5

Telephone: 450-586-2252
Order Desk: 800-363-1700
Fax: 450-586-4649
Website: www.vetoquinol.ca
Email: info@vetoquinol.ca



Every effort has been made to ensure the accuracy of the information published. However, it remains the responsibility of the readers to familiarize themselves with the product information contained on the product label or package insert.

BIOFOAM

Vétoquinol

MULTIPURPOSE HEAVY DUTY CLEANER

FOAMING DESCALING DETERGENT

powerful foaming cleaning concentrate

superior degreasing properties

for use in food processing hatcheries & on the farm

biodegradable

APPLICATION: For the removal of organic and inorganic residues particularly the build up of scale. **Antec Biofoam** is ideal for the removal of soiling in hatcheries and processing plants where humidity can cause soil and scale build up. **Antec Biofoam** will also help to remove stubborn staining and soiling on factory floors and stats on livestock farms.

COMPOSITION: A synergistic blend of surfactants which combine to produce a superior foaming cleaner, preventing the build up of scale.

DIRECTIONS FOR USE:

DILUTION RATES: in normal use Biofoam should be used at a dilution rate of between 0.5% - 5% dependant on soiling and scaling levels. In situations where there are thick build-ups of scaling and soil it may be necessary to use Biofoam at a higher concentration rate of up to 10%.

SPRAYING: Apply at a rate of 500 mL per m² with either a knapsack sprayer or pressure washer. The pressure washer should be set on a low pressure setting (500 psi - 35 bars) using a 45 degrees jet angle. Hot water will improve the effectiveness of the product. Allow a contact time of 15 minutes prior to rinsing all surfaces thoroughly with water at high pressure (3000 psi - 207 bars). For personal comfort when spraying the product, wear a suitable mist respirator.

FOAMING: Apply at a rate of 250 mL per m² with a pressure washer set on a low pressure setting (500 psi - 35 bars). Hot water will improve the effectiveness of the product. Allow a contact time of 15 minutes prior to rinsing all surfaces thoroughly with water at high pressure (3000 psi - 207 bars).

STAIN REMOVAL: For awkward stains and established scale build-ups **Antec Biofoam** may be used pure.

Precautions: Do not allow product to enter any watercourses. Do not allow product to freeze. Irritating to eyes and skin. Keep out of reach of children. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Distributed by: Vétoquinol N.-A. Inc., 2000, ch. Georges, Lavaltrie, QC, Canada J5T 3S5

www.vetoquinol.ca

Manufactured by: Antec International Ltd., Windham rd, Chilton Industrial Estate, Sudbury, Suffolk CO10 2XD UK

Tel: +44 (0) 1787 377305

Fax: +44 (0) 1787 310846

Web: www.antecint.com

E-mail: biosecurity@antecint.com

NET CONTENTS	CODE :	
20 L	11766	02.03

NAC No.: 12342480